



TWT Amplifier

12-18GHz, 2kW, 6% Duty
RTWTA-12-18-2kW-6%-w9



ELECTRICAL	
Frequency Range:	12-18 GHz
Output power Psat.	63 dBm Nominal (2kW rated)
Input power	0 dBm for 2kW out
Duty	6% maximum
Spurious for 0-250Hz	-55 dBc max.
Spurious for >250Hz	-60 dBc max.
Output VSWR protection	
Output pulse video sample	+10 mV/kW into 50Ω
Output Pulse sample	-30 dB
Input Power sample	-20 dB
MODULATION	
Pulse width	0.1 to 25μs
Pulse repetition rate	0-10 KHz
Rise and fall time	20ns max.
Droop	0.01 dB/ μs
Pulse jitter	±2ns
Video/RF delay	300ns max.
Modulation input pulse	+5V TTL
Primary Power: Nema L5-20 (3 wire)	
Voltage:	115 ±10%, single phase
Primary Power Consumption	2.1KVA max.
Frequency:	60 Hz
Elapsed time meter	100,000.0 hrs
MECHANICAL	
Dimensions:	19" x 8.75" x 35" deep (Rack)
Weight:	85 Pounds typical
Finish	Front: Enamel FSN 26440 Grey Chassis: Gold Alodine
RF Connectors:	
Input:	Type-N (f) on rear panel
Output:	Waveguide WR-62 on rear panel
RF Sample Ports	Type-N (f) on front panel
Input Pulse	Standard TTL level, BNC (f) 50 Ω on rear panel
RF output video pulse	Standard TTL level, BNC (f) 50 Ω on front panel

ENVIRONMENTAL	
Temperature:	0°C to +50°C
Operating	(derate 10°C per 10,000 feet altitude)
Storage:	-30°C to +60°C
Humidity:	0-95% non condensing
Altitude	To 10,000 feet (-30 to 60°C)
MONITOR & CONTROL	
Computer Interface:	IEEE-488 (GPIB) rear panel (optional) Ethernet RJ45 rear panel (optional) RS 232 DB25 rear panel
Conditions monitored and interlocked.	
VSWR	
Body Voltage	xx.xx KV
Body current	xx.xx mA
Heater Voltage	x.xx V
Heater Current	x.xx A
Grid bias voltage	xxx.xx V
Grid Pulse amplitude	xxx.xx V
Lid Access interlock	Fault
Over temperature	Fault
PRF limit	Fault
Pulse width limit	Fault
Pulse received	Yes/No

RS 232 interface allows remote operation, monitor, control; and adjustment. Any fault condition latched the information. Windows compatible MS GUI is supplied. The following Parameters. have high and low limits that are factory adjustable, Cathode Voltage, Body Current, Heater Voltage, Heater current, Grid bias voltage, Grid Pulse Amplitude, PRF limit, Pulse width Limit. Self contained forced air cooling.