


RADITEK INC.

Dielectric Band Pass Filter 1595-1755MHz, Surface Mount RBPF-1595-1755M-S

code-q

ELECTRICAL SPECIFICATIONS			
ITEM		SPEC	Unit
1	Center Frequency [fo]	1675.0	MHz
2	Bandwidth [BW]	$f_o \pm 80$	MHz
3	Insertion Loss in BW	2.0.	dB max
4	Ripple in BW	0.5.	dB max
5	VSWR in BW	1.5 max	Ratio
6	Attenuation [Absolute Value]	10 dB min. @ 1300 - 1500 MHz 30 dB min. @ 1850 - 2100 MHz 20 dB min. @ DC - 1000 MHz 60.0 dB min. @ 2200 MHz	
7	In/Out Impedance	50 Ω	
8	Operation Temperature Range	-40°C to +85°C	

DIMENSIONS



RBPF-1595-1755M-S-q

Specifications may be subject to change

03/29/07

WORLD HQ: 1702L Meridian Ave. Suite 127, San Jose, Ca 95125, U.S.A.

Telephone: (408) 266-7404 FAX: (408) 266-4483

WEB: www.raditek.com, E-mail: sales@raditek.com

RADITEK INC.

Dielectric Band Pass Filter 1595-1755MHz, Surface Mount RBPF-1595-1755M-S

code-q

