

RADITEK INC.


Surface Acoustic Wave Band Pass Filter 890-915MHz, Model 0303, Surface Mount RSAW-BPF-890-915M-0303-S-g2

code-g2

ELECTRICAL SPECIFICATIONS:

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	-	902.500	-
3db Bandwidth	MHz	-	±19	-
Usable Bandwidth	MHz	-	±15	-
Insertion Loss (887.50-917.50MHz)	dB	-	2.7	3.6
Amplitude Variation (p-p)(887.50-917.50MHz)	dB	-	1.0	1.8
Absolute Attenuation DC-840.00MHz	dB	48	57	-
930.00-990.00MHz		20	28	-
990.00-2000.00MHz		48	58	-
Input/ Output Impedance	Ω	50		
dBm	dBm	10		
DC Voltage	V	12		
Storage Temperature	°C	-40 to +85		
Operating Temperature	°C	-10 to +65		

PACKAGE DIMENSIONS:



Pin	Configuration
2	Input
5	Output
1,3,4,6	Ground

Sign	Data (unit: mm)	Sign	Data (unit: mm)
A	0.6	E	1.1
B	1.5	F	3.0
C	1.5	G	3.0
D	1.8		

RSAW-BPF-890-915M-0303-S-g2

Specifications may be subject to change

02/18/09

WORLD HQ: 1702L Meridian Ave. Suite 127, San Jose, Ca 95125, U.S.A.

Telephone: (408) 266-7404 FAX: (408) 266-4483


WEB: www.raditek.com, E-mail: sales@raditek.com

RADITEK INC.

Surface Acoustic Wave Band Pass Filter 890-915MHz, Model 0303, Surface Mount RSAW-BPF-890-915M-0303-S-g2

code-g2

Matching Circuit:



Typical Frequency Response:

